


## I Ruote con 2 cuscinetti predisposte per perno ingrassatore - gola V ANGULA


- UK Wheels with two bearings preset for lubricator pin - V groove
- D Laufrollen mit zwei Lagern - V Nut
- F Roues avec 2 roulements pour axes avec graisseur - gorge V
- E Ruedas con 2 cojinetes preparadas para ingrassador - guía V
- RUS Ролик нормальный с 2 подшипниками для оси с масленкой паз V



Articolo - Article	D	d1	F	A	C	Portata Capacity	
<b>Riferimento - Reference</b>		∅		mm	V	x1	
10030 I V RT 10 30 V3	100	80	20	30	96°	350	12 15,2
12030 I V RT 12 30 V3	120	100	20	30	96°	380	8 15,7
14030 I V RT 14 30 V3	140	120	20	30	96°	400	4 11,4
16038 I V RT 16 38 V3	160	133	20	38	96°	520	2 9,3
18038 I V RT 18 38 V3	180	153	20	38	96°	560	2 12
20038 I V RT 20 38 V3	200	173	20	38	96°	600	2 15
25038 I V RT 25 38 V3	250	223	20	38	96°	700	2 24,6

## I Ruote con 2 cuscinetti predisposte per perno ingrassatore - gola U


- UK Wheels with two bearings preset for lubricator pin - U groove
- D Laufrollen mit zwei Lagern - U Nut
- F Roues avec 2 roulements pour axes avec graisseur - gorge U
- E Ruedas con 2 cojinetes preparadas para ingrassador - guía U
- RUS Ролик нормальный с 2 подшипниками для оси с масленкой паз U



Articolo - Article	D	d2	F	A	C	Portata Capacity	
<b>Riferimento - Reference</b>		∅		mm	U	x1	
10030 I U RT 10 30 U3	100	78	20	30	21	350	12 13,1
12030 I U RT 12 30 U3	120	98	20	30	21	380	8 13,8
14030 I U RT 14 30 U3	140	120	20	30	21	400	4 10,2
16038 I U RT 16 38 U3	160	140	20	38	21	520	2 9
18038 I U RT 18 38 U3	180	158	20	38	21	560	2 11,8
20038 I U RT 20 38 U3	200	178	20	38	21	600	2 14,7
25038 I U RT 25 38 U3	250	228	20	38	21	700	2 24

## I Ruote con 2 cuscinetti predisposte per perno ingrassatore - gola O per


- UK Wheels with two bearings preset for lubricator pin - O groove  
 D Laufrollen mit zwei Lagern - O Nut  
 F Roues avec 2 roulements pour axes avec graisseur - gorge O  
 E Ruedas con 2 cojinetes preparadas para ingrassador - guía O  
 RUS Ролик нормальный с 2 подшипниками для оси с масляной паз O



Articolo - Article		D	d3	F	A	C	Portata Capacity		
Riferimento - Reference		∅		mm		O	⊗ x1	N°	⊗
10030 I O	RT 10 30 03	100	81	20	30	21	350	12	14,6
12030 I O	RT 12 30 03	120	101	20	30	21	380	8	15,1
14030 I O	RT 14 30 03	140	121	20	30	21	400	4	10,9
16038 I O	RT 16 38 03	160	141	20	38	21	520	2	9,5
18038 I O	RT 18 38 03	180	161	20	38	21	560	2	12,2
20038 I O	RT 20 38 03	200	181	20	38	21	600	2	15,3
25038 I O	RT 25 38 03	250	231	20	38	21	700	2	24,9

## I Perni ingrassatori

- UK Lubricator pins  
 D Achse mit Schmiernippel  
 F Axes avec graisseur  
 E Pernio ingrassador  
 RUS Ось с масляной



Per ruote art. 10030 I - 12030 I - 14030 I

Articolo - Article		B	FxL
Riferimento - Reference		mm	UNI
B1 - 40	IT 16 50 G0	34	M 16x50
B1 - 50	IT 16 60 G0	44	M 16x60
B1 - 60	IT 16 70 G0	54	M 16x70
B1 - 80	IT 16 90 G0	74	M 16x80
B1 - 100	IT 16 12 G0	94	M 16x120

Per ruote art. 16038 I - 18038 I - 20038 I - 25038 I

Articolo - Article		B	FxL
Riferimento - Reference		mm	UNI
B2 - 50	IT 20 60 G0	44	M 20x60
B2 - 60	IT 20 70 G0	54	M 20x75
B2 - 80	IT 20 90 G0	74	M 20x90
B2 - 100	IT 20 12 G0	94	M 20x120