

ANGULA

I Ruote con supporto esterno a 1 cuscinetto - gola V per


UK Wheels with outer support with one bearing - V groove

D Laufrollen mit Stützplatten und einem Lager - V Nut

F Roues à 1 roulement avec support externe - gorge V

E Ruedas con soporte externo con 1 cojinete - guía V

RUS Ролик с 1 подшипником с наружным кронштейном паз V




| Articolo - Article | | D | d1 | A | B | C | G | S | E | LxHxS | Portata Capacity | | |
|-------------------------|-------------|-----|-----|----|----|-----|-----|---|------|----------|------------------|----|------|
| Riferimento - Reference | | ∅ | | mm | | V | mm | | | mm | kg x1 | N° | kg |
| 820 PV | RT 80 20 VP | 80 | 65 | 20 | 30 | 96° | 62 | 3 | 9,5 | 70x40x3 | 140 | 12 | 9,2 |
| 920 PV | RT 90 20 VP | 90 | 75 | 20 | 30 | 96° | 71 | 3 | 10,5 | 80x40x3 | 160 | 12 | 12 |
| 1020 PV | RT 10 20 VP | 100 | 85 | 20 | 30 | 96° | 82 | 3 | 9,5 | 90x40x3 | 180 | 12 | 15,4 |
| 1220 PV | RT 12 20 VP | 120 | 105 | 20 | 30 | 96° | 99 | 3 | 12 | 110x40x3 | 200 | 8 | 15,5 |
| 1420 PV | RT 14 20 VP | 140 | 125 | 20 | 30 | 96° | 116 | 3 | 16,5 | 120x40x3 | 230 | 4 | 10,8 |

Ruote

I Ruote con supporto esterno a 1 cuscinetto - gola U


- UK Wheels with outer support with one bearing - U groove
- D Laufrollen mit Stützplatten und einem Lager - U Nut
- F Roues à 1 roulement avec support externe - gorge U
- E Ruedas con soporte externo con 1 cojinete - guía U
- RUS Ролик с 1 подшипником с наружным кронштейном паз U



| Articolo - Article | | D | d2 | A | B | C | G | S | E | LxHxS | Portata Capacity | | |
|-------------------------|-------------|-----|-----|----|----|---|-----|---|------|----------|------------------|----|------|
| Riferimento - Reference | | ∅ | | mm | | U | mm | | mm | mm | kg x1 | N° | kg |
| 820 PU | RT 80 20 UP | 80 | 65 | 20 | 30 | 7 | 62 | 3 | 10 | 70x40x3 | 140 | 12 | 9,2 |
| 920 PU | RT 90 20 UP | 90 | 75 | 20 | 30 | 7 | 71 | 3 | 11 | 80x40x3 | 160 | 12 | 12 |
| 1020 PU | RT 10 20 UP | 100 | 85 | 20 | 30 | 7 | 82 | 3 | 10 | 90x40x3 | 180 | 12 | 15,4 |
| 1220 PU | RT 12 20 UP | 120 | 105 | 20 | 30 | 7 | 99 | 3 | 12,5 | 110x40x3 | 200 | 8 | 15,5 |
| 1420 PU | RT 14 20 UP | 140 | 125 | 20 | 30 | 7 | 116 | 3 | 16 | 120x40x3 | 230 | 4 | 10,8 |

I Ruote con supporto esterno a 2 cuscinetti - gola V per ANGULA


- UK Wheels with outer support with two bearings - V groove
- D Laufrollen mit Stützplatten und zwei Lagern - V Nut
- F Roues à 2 roulements avec support externe - gorge V
- E Ruedas con soporte externo con 2 cojinetes - guía V
- RUS Ролик с 2 подшипниками с наружным кронштейном паз V



| Articolo - Article | | D | d1 | A | B | C | G | S | E | LxHxS | Portata Capacity | | |
|-------------------------|-------------|-----|-----|----|----|-----|-----|---|-----|----------|------------------|----|------|
| Riferimento - Reference | | ∅ | | mm | | V | mm | | mm | mm | kg x1 | N° | kg |
| 1030 PV | RT 10 30 VP | 100 | 80 | 30 | 42 | 96° | 82 | 3 | 7 | 90x50x3 | 300 | 12 | 18,1 |
| 1230 PV | RT 12 30 VP | 120 | 100 | 30 | 42 | 96° | 99 | 3 | 9,5 | 110x50x3 | 350 | 6 | 15,5 |
| 1430 PV | RT 14 30 VP | 140 | 120 | 30 | 42 | 96° | 116 | 3 | 13 | 120x50x3 | 400 | 4 | 14,7 |

I Ruote con supporto esterno a 2 cuscinetti - gola U

- UK Wheels with outer support with two bearings - U groove
- D Laufrollen mit Stützplatten und zwei Lagern - U Nut
- F Roues à 2 roulements avec support externe - gorge U
- E Ruedas con soporte externo con 2 cojinetes - guía U
- RUS Ролик с 2 подшипниками с наружным кронштейном паз U




| Articolo - Article | | D | d2 | A | B | C | G | S | E | LxHxS | Portata Capacity | | |
|-------------------------|-------------|-----|-----|----|----|----|-----|---|------|----------|------------------|----|------|
| Riferimento - Reference | | ∅ | | mm | | U | mm | | mm | mm | kg x1 | N° | kg |
| 1030 PU | RT 10 30 UP | 100 | 80 | 30 | 41 | 21 | 82 | 3 | 6 | 90x50x3 | 300 | 12 | 18,1 |
| 1230 PU | RT 12 30 UP | 120 | 98 | 30 | 41 | 21 | 99 | 3 | 8,5 | 110x50x3 | 350 | 6 | 15,5 |
| 1430 PU | RT 14 30 UP | 140 | 118 | 30 | 41 | 21 | 116 | 3 | 12,5 | 120x50x3 | 400 | 4 | 14,7 |

Ruote

I Ruote con supporto esterno a 2 cuscinetti - gola O per



- UK Wheels with outer support with two bearings - O groove
- D Laufrollen mit Stützplatten und zwei Lagern - O Nut
- F Roues à 2 roulements avec support externe - gorge O
- E Ruedas con soporte externo con 2 cojinetes - guía O
- RUS Ролик с 2 подшипниками с наружным кронштейном паз O



| Articolo - Article | | D | d3 | A | B | C | G | S | E | LxHxS | Portata Capacity | | |
|-------------------------|-------------|-----|-----|----|----|----|-----|---|------|----------|------------------|----|------|
| Riferimento - Reference | | ∅ | | mm | | O | mm | | | mm | kg x1 | N° | kg |
| 830 PO | RT 80 30 OP | 80 | 61 | 30 | 42 | 21 | 62 | 3 | 7,5 | 80x50x3 | 250 | 12 | 15,6 |
| 1030 PO | RT 10 30 OP | 100 | 81 | 30 | 42 | 21 | 82 | 3 | 7,5 | 90x50x3 | 300 | 12 | 18,1 |
| 1230 PO | RT 12 30 OP | 120 | 101 | 30 | 42 | 21 | 99 | 3 | 10 | 110x50x3 | 350 | 6 | 15,5 |
| 1430 PO | RT 14 30 OP | 140 | 121 | 30 | 42 | 21 | 116 | 3 | 15,5 | 120x50x3 | 400 | 4 | 14,7 |