

4000 Series Audio/Video Modules

4000 Series VX2300 Digital System Audio/Video Speaker & Camera Modules with Integrated Proximity



Art.	4384X-0	4384X-1	4384X-2
DESCRIPTION	Modular 4000 series VX2300 digital system audio/video speaker & colour camera with integrated proximity		
BUTTONS	BUILT-IN 0	1	2
MAX.	multiple combinations (up to 94 max.) with additional button modules: 4042...4045 and 4042D...4045D with IDC ribbon cables CFL17 and CFL45		
CAMERA: CAMERA LENS/ LED/ CAMERA TILT	CMOS colour camera with auto iris lens / 4x white illumination LED's / 10° tilt angle (horizontal and vertical adjustment)		
FRONT FASCIA OPTIONS	Mirror Stainless Steel, /M Matt 316 Marine Grade Stainless Steel		
WIDE ANGLE OPTION	Available /W : 170° viewing angle		
INTEGRATED PROXIMITY ACCESS	Yes: up to 50 users (max.), operating RFID frequency 125kHz (built-in proximity reader behind nameplate window for button 1)		
COMPATIBLE FOBS & CARDS	Fobs: 955/T (blue), 955/B (black), 955/R (red), 955/Y (yellow), 955/G (green), card: 955/C		
NAME PLATE & BACK LIGHT	Yes: 1 (proximity window)	Yes: 1 (backlit blue)	Yes: 2 (backlit blue)
CALL PROGRESS LED'S	Yes: 4x LED's, Busy, Call, Speak and Door Open with reassurance tones		
MODULE PROGRAMMING	8 Way Switch: Unit ID (ID's 1 - 15); Door Open Time; Conversation Time; Push Button Group configuration; standard / advanced Programming Modes.		
RS485 CONNECTIVITY	Yes: RS485 bus connection used for programming with 2X00PC software (via a 481 RS485/USB converter) and when set to advanced programming mode.		
MODULE SIZE	1 module 4000 series: 103 (W) x 120 (L) x 30 (D) mm		
MOUNTING HEIGHT	between 130 - 160cm (approx.)		
ILLUMINATION DISTANCE (LED'S)	up to 50cm (max.)		
ADJUSTMENT POTS	Yes: Microphone, Speaker and Balance		
RELAY CONTACTS	1x Dry Contact (C/NO/NC) / Capacitor Discharge (+C linked to relay contact C)		
RELAY VOLTAGE / AMPS	Dry Contact Voltage/Current Rating: 12V-24Vac/dc 2A max.		
PTE INPUT	Yes: 1x PTE switched 0V input (push-to-make)		
WORKING VOLTAGE	32 - 35Vdc Powered by BUS (BUS voltage supplied by 2321 or 2321P PSU)		
POWER CONSUMPTION	Standby: 50mA / During Operation: 165mA		
WORKING TEMP.	-10° to +50°C		



955/T



955/B



955/R



955/Y



955/G



955/C

