

# 4000 Series Audio Modules

4000 Series "4+1" Audio Speaker Modules



AUDIO  
MODULE



STANDARD  
4+1 AUDIO



Art. 4837-0



Art. 4837-1



Art. 4837-2



Art. 4837-0/M



Art. 4837-1/M



Art. 4837-1D/M



Art. 4837-2/M



Art. 4837-2D/M

Art.	4837-0	4837-1	4837-1D	4837-2	4837-2D	
<b>DESCRIPTION</b>	Modular 4000 series "4+1" audio speaker					
<b>BUTTONS</b>	<b>BUILT-IN</b>	0	1	2	2	4
	<b>MAX.</b>	multiple combinations with the use of additional button modules: <b>4842, 4843, 4844, 4845, 4842D, 4843D, 4844D and 4845D</b>				
<b>FRONT FASCIA OPTIONS</b>	Mirror Stainless Steel, /M Matt 316 Marine Grade Stainless Steel					
<b>NAME PLATE &amp; BACK LIGHT</b>	No	Yes: 1 (backlit blue)		Yes: 2 (backlit blue)		
<b>CALL PROGRESS LED'S</b>	N/A					
<b>MODULE PROGRAMMING</b>	N/A					
<b>MODULE SIZE</b>	1 module 4000 series: 103 (W) x 120 (L) x 30 (D) mm					
<b>ADJUSTMENT POTS</b>	Yes: Microphone and Speaker					
<b>NO. OF RELAYS</b>	1 internal relay					
<b>RELAY CONTACTS</b>	Normally Open Contacts S/S1 (C/NO pair)					
<b>RELAY VOLTAGE / AMPS</b>	Dry Contact Voltage/Current Rating: 24Vac/dc 2A max.					
<b>PTE INPUT</b>	Yes: 1x RL switched 0V input (push-to-make)					
<b>WORKING VOLTAGE</b>	+12Vdc (compatible PSU's: <b>520M</b> and <b>521B</b> )					
<b>POWER CONSUMPTION</b>	Stand-by: 25mA / During Call: 150mA / During Conversation: 70mA					
<b>WORKING TEMP.</b>	-10° to +50°C					