

# 4000 Series Camera Modules

4000 Series Colour Camera Modules



**CAMERA  
MODULE**



**NON-COAX  
VIDEO**



**COAX  
VIDEO**



**WIDE  
ANGLE  
CAMERA OPT.**



**Art. 4830/C/A**

**Art. 4830/C**

**Art. 4830/C/HB**

**Art. 4830/C**

Art.	4830/C
<b>DESCRIPTION</b>	Modular 4000 series colour camera
<b>CAMERA:</b> <b>CAMERA LENS/</b> <b>LED/</b> <b>CAMERA TILT</b>	CCD colour camera with auto iris lens / 6x white illumination LED's / 10° tilt angle (horizontal and vertical adjustment)
<b>FRONT FASCIA OPTIONS</b>	Stainless Steel (standard), <b>/A</b> Anodized Aluminium, <b>/HB</b> High Brass
<b>WIDE ANGLE OPTION</b>	Available <b>/WD</b> : 170° viewing angle
<b>MODULE SIZE</b>	1 module 4000 series: 103 (W) x 120 (L) x 30 (D) mm
<b>ADJUSTMENTS</b>	Jumpers: video signal mode selection - balanced (V1/V2) or coax (V/M)
<b>SYSTEM COMPATIBILITY</b>	Can be configured to work on systems with coax video signal, traditional "9+coax" video. Can also be configured to work with VX2200 digital video systems, non-coax (balanced) or coax video signal, as well as VX2000 digital video systems.
<b>MOUNTING HEIGHT</b>	between 130 - 160cm (approx.)
<b>ILLUMINATION DISTANCE (LED's)</b>	up to 50cm (max.)
<b>WORKING VOLTAGE</b>	14 - 20Vdc (compatible with <b>893N</b> )
<b>POWER CONSUMPTION</b>	Max. During Operation: 200mA
<b>WORKING TEMP.</b>	-10° to +50°C

