

4000 Series Standalone Proximity Module

4000 Series 99 User Standalone Proximity Module



Art.	4850
DESCRIPTION	Modular 4000 series standalone 99 user proximity module
FRONT FASCIA OPTIONS	Mirror Stainless Steel, /M Matt 316 Marine Grade Stainless Steel, /BL Gun Metal Grey
INDICATION LED'S & PROGRAMMING LED'S	Yes: Tri-colour indication LED (front), amber = standby, green = access granted, red = access denied. Program setup LED's (back), 2x yellow (TENS, UNITS), 1x green (STORE) and 1x red (DELETE)
NUMBER OF USERS	Up to 99 users max.
COMPATIBLE FOBS / CARDS	Fobs: 955/T (blue), 955/B (black), 955/R (red), 955/Y (yellow), 955/G (green), card: 955/C
PROGRAMMABLE RELAY TIMES	Relay times 1 - 99 seconds or 00 for latching
PROGRAMMING METHOD	Programming & setup LED's & buttons (back), 2x yellow (TENS, UNITS), 1x green (STORE) and 1x red (DELETE)
MODULE SIZE	1 module 4000 series: 103 (W) x 120 (L) x 30 (D) mm
RELAY CONTACTS	1 Dry Contact Relays: C/NO/NC
RELAY VOLTAGE / AMPS	Dry Contact Voltage/Current Rating: 24Vac/dc 3A max.
PTE INPUT	Yes: 1x switched 0V input (push-to-make), PTE
WORKING VOLTAGE	12-24Vac or dc (compatible PSU's: 321 , 322 and HDR-15-12)
POWER CONSUMPTION	Stand-by: 80mA, During Operation: 120mA (max.)
WORKING TEMP.	-10° to +50°C