



Specification:

Maximum Span

12.0 Metres

Maximum Height

3.5 Metres (depending on span)

Opening/closing time:

5 Seconds per metre (adjustable)

Drive unit:

3 Phase Motor & Wormed Gearbox Rack and pinion

Safety :

Category 3 Bircher Edges
Dual Height Photocells

Cycles:

100 % Duty Cycle

Dimensions: Stanchion

1000mm x 600mm

Power Supply:

230 v ac 50hz 6amp

The Ultimation Direct 5800 Cantilever Sliding Gate is custom built to the individual's requirements and to the highest security specifications. These gates although mainly designed for high use sites will compliment any business or home. A wide variety of infill's are available from palisade to solid. These gates are for very wide openings of 6 m to 12 m.

The 5800 series of incorporates a 3-phase inverter motor/gearbox drive which provides smooth consistent operation with variable speed. This is all controlled via a SIEMENS PLC, which can be programmed to suit any access control requirements and also features adjustable parameters that make it very installer friendly. All our gates are fully set up and tested in house to minimise install time on site. With a built in slow down feature that can be adjusted on site to allow the installer to force test and it pass with ease.



COMPLIES WITH
SAFETY STANDARD
BS/EN 12453

BIRCHER
Regomat

Made in
the 

"THE ULTIMATE SLIDING GATE"



**MANY INFILL'S
AVAILABLE**