

4000 Series Audio Modules

4000 Series “4+1” & “5+1” Audio Speaker Modules



AUDIO
MODULE



STANDARD
4+1 AUDIO



SENTRY
5+1 AUDIO



Art. 4838-0



Art. 4838-1



Art. 4838-2



Art. 4838-0/M



Art. 4838-1/M



Art. 4838-1D/M



Art. 4838-2/M



Art. 4838-2D/M

Art.	4838-0	4838-1	4838-1D	4838-2	4838-2D	
DESCRIPTION	Modular 4000 series “4+1” & “5+1” audio speaker					
BUTTONS	BUILT-IN	0	1	2	2	4
	MAX.	multiple combinations with the use of additional button modules: 4842, 4843, 4844, 4845, 4842D, 4843D, 4844D and 4845D				
FRONT FASCIA OPTIONS	Mirror Stainless Steel, /M Matt 316 Marine Grade Stainless Steel					
NAME PLATE & BACK LIGHT	No	Yes: 1 (backlit blue)		Yes: 2 (backlit blue)		
CALL PROGRESS LED'S	Yes: 4x LED's, Busy, Call, Speak and Door Open					
MODULE PROGRAMMING	SW1: Call tone selection; No. of Rings (“5+1” system only); Conversation Time; Door Open Time SW2: Reassurance Tone (ON/OFF); System Type (“4+1” or “5+1”); Automatic recall when handset lifted (“4+1” system only)					
MODULE SIZE	1 module 4000 series: 103 (W) x 120 (L) x 30 (D) mm					
ADJUSTMENT POTS	Yes: Microphone and Speaker					
NO. OF RELAYS	1 internal relay					
RELAY CONTACTS	Dry Contacts (C/NO/NC)					
RELAY VOLTAGE / AMPS	Dry Contact Voltage/Current Rating: 24Vac/dc 2A max.					
PTE INPUT	Yes: 1x PTE switched 0V input (push-to-make)					
WORKING VOLTAGE	+12Vdc (compatible PSU's: 520M and 521B)					
POWER CONSUMPTION	Stand-by: 25mA / During Call: 150mA / During Conversation: 70mA					
WORKING TEMP.	-10° to +50°C					