

INTRABOX DATA PROX

Secure access control

INTRABOX



reader (04-0106) + 1 relay card (12-0110) + 1 transmission module unlimited data and syncing for 10 years (06-0131).

- ▶ No need for a programmer
- Create, change or delete key fobs without recovering them
 SQUARE PROXIMITY
- > Stainless steel finish



Accessible for all







Remote online management www.intratone.info

READER 04-0106



ruictions	
Free access time slots	Yes
Log events	Yes
Compatible with key fobs and remote transmitters equipped with MIFARE technology	Yes
Maximum number of key fobs / master key fobs	10,000
Technical alerts (emails)	~

TECHNICAL SPECIFICATIONS

Power supply

min. 12/24 V DC - 2 A

Relay card - reader
4 wires (2 twisted pairs)

Wiring

Ø 8/10e - Max: 200m Relay card - GPRS unit 4 wires (2 twisted pair)

Ø 8/10e - Max: 200m

Dimensions (L x H x D)

Reader 32 x 42 x 18mm Relay card 74 x 59 x 18mm GPRS unit 162 x 96 x 53mm Read head (with cover)

64.5 x 62 x 23mm Read head only Ø 40 x 40mm Reader (bare) 62 x 62 x 23mm

Environment

Reader operating temperature
-20°C to +70°C
Reader storage temperature
-20°C to +70°C

Reader protection class IP50

SIMPLIFIED SCHEMATIC



RANGE

100M MAX. TWISTED PAIR $5/10^{\rm F}$ - 200M MAX. TWISTED PAIR $8/10^{\rm F}$

Products

06-0143 Intrabox Data Prox: 2 flush fit square proximity readers (04-0106) + 2 door controller for 2 doors (03-0101) + 1 transmission module unlimited data and syncing for 10 years

OS 0121
Intrabox Data Prox: 1 flush fit square proximity reader (04-0106) + 1 relay card (12-0110) + 1 transmission module unlimited data

o6-0131 and syncing for 10 years

Accessory

12-0132 Surface mounted box for square reader - surface mounted - stainless steel finish (125.5 x 125.5 x 57mm)

Box for square reader - flush-fit - stainless steel finish (90.4 x 90 x 37mm)

87