



SECURITY PRODUCT SUPPLIES

SPS-MAGLOCK

K-500KGAW 4Wires	12V & 24V adjustable
Lock Size	222Lx62Wx38H(mm)
Armature plate	195Lx61Wx15H(mm)
Holding Force	500kg(1200Lbs)
Voltage	DC12V or DC24V(adjustable)
Current Draw	12V/420mA 24V/210mA
Optional Bracket	K-500ZL
Suitable for	Wooden door, Glass door, Metal door, Fireproof door
Surface Temp	≤20°C
Operating Temp	-10°C ~ 55°C (14°F-131°F)
Suitable Humidity	0~90%(non-condensing)
Finishes for Shell	Anodized aluminum
Finishes for Magnetic	Zinc
Finishes for Armature	Zinc
Weight	4.5kg


A.12VDC Input:



- Red → The red line and yellow line is connected to DC12V (+) pole.
- Yellow → The blue line and black line is connected to DC12V (-) pole.
- Blue →
- Black →
- White (COM)
- Brown (NC)
- Green (NO)

(NO/NC/COM for optional)

B.24VDC Input:



- Red → The red line is connected to DC24V (+) pole.
- Yellow → The yellow line and blue line connected.
- Blue →
- Black → The black line is connected to DC24V (-) pole.
- White (COM)
- Brown (NC)
- Green (NO)